

CITY OF ODESSA
STANDARD SPECIFICATIONS

ITEM 24
RESHAPING BASE COURSE

24.1 DESCRIPTION

This item shall consist of reshaping and refinishing the surface of the existing base as herein specified and in conformity with the typical sections shown on plans and the line and grades established by the Engineer.

24.2 CONSTRUCTION METHODS

The surface of the existing base shall first be thoroughly cleaned of all dirt and other objectionable material by blading, supplemented by brooming or other approved methods. All holes, ruts, depressions in the surface or existing surfacing shall be repaired by scarifying where required, reshaping, sprinkling, and rolling as directed until a uniform compaction is secured. The rolling shall be performed as directed. Throughout this entire operation, the shape of the course shall be maintained by blading, and the surface upon completion shall be smooth and in conformity with the typical sections shown on plans and to the established lines and grades in that area on which pavement is to be placed. Any deviation in excess of one-quarter (1/4) inch in cross section and in a length of sixteen (16) feet measured longitudinally, shall be loosened, reshaped and recompactd by sprinkling and rolling.

24.3 MEASUREMENT

Reshaping base course performed as provided above will be measured by the square yard of base course surface reshaped.

24.4 PAYMENT

The work performed as prescribed by this item and measured as provided under "Measurement" will be paid for at the contract unit price bid for "Reshaping Base Course" which price shall be full compensation for furnishing and operating all equipment necessary to satisfactorily perform the work and for furnishing all labor, fuel, tools and incidentals required, including sprinkling and rolling.